

# TECHNICAL DATA SHEET

REVISED: 02/12/2022

## ADHESIVA 2PG

ADHESIVES FOR VINYL, LVT AND RUBBER FLOORINGS

ADHESIVES FOR WOODEN FLOORINGS



Structural two-component epoxy-polyurethane adhesive (A+B), suitable for installing rubber, contract flooring and both indoor and outdoor sports floorings, pre-finished parquet or hardwood of any kind.

Suitable for:

- High traffic cushioned flooring in tiles or roll
- Vinyl floorings on cement, marble or ceramic
- Cushioned flooring, including natural rubber, with smooth or textured backing including for outdoor use
- Synthetic grass
- Pre-finished parquet
- Laminated parquet
- Hardwood of any thickness

### TECHNICAL FEATURES:

- + Solvent free
- + Low shrinkage
- + Strong grip

### PREPARATION OF SURFACE

All grounds and surfaces must be dry, porous, dust-free and free from paint and oil. Any gaps should be sealed using our 2-part epoxy adhesive EPOXY ECO. The surface should have a maximum humidity: Cement max 3%; Gypsum max 0.5%. On uneven surfaces we recommend using a cement-based auto-levelling screed. To further improve the levelling, we also suggest using our VISOLYN ST100 in a 10% addition to the levelling screed. We always recommend the use of our PRIMER AC sealant for consolidation and cleanliness.

### PREPARATION OF MATERIALS

Before commencing installation, we suggest leaving the materials on site for one day prior to commencing work for it to be done at room temperature. Apply the product in accordance with the manufacturer's recommended installation temperature. Carefully unpack or unroll the product to permit it to relax and reduce creasing.

### PREPARATION OF PRODUCT

Combine component B (hardener) with component A (resin base from the larger bag) and mix together until the two components are the same colour. We recommend using a low-speed electric mixer for about 5 minutes

### APPLYING THE PRODUCT

Spread the adhesive mix with a grooved spatula (see below). Use a n°2/3 grooved spatula directly on the flooring to be laid. Apply it so the adhesive coats every contact surface.

### CLEANING

We recommend cleaning tools using a nitro thinner.

# TECHNICAL DATA SHEET

REVISED: 02/12/2022

## ADHESIVA 2PG

ADHESIVES FOR VINYL, LVT AND RUBBER FLOORINGS

ADHESIVES FOR WOODEN FLOORINGS



### ADVICE

- Do not use at temperatures below 10°C
- We recommend operating temperatures between + 10°C & 35°C
- Treat non-absorbent surfaces so that they become porous.

### COVERAGE

800-1000 g/m<sup>2</sup>

### PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
20047-5-N	5	kg	Bucket	1
20048-10-N	10	kg	Bucket	1

### STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

### PRODUCT TECHNICAL DATA

Base	Epoxy-polyurethane
Physical appearance	Cream beige or coloured upon request
Ratio	9:1
Percentage of solids	Around 60%
Customs code	(AeB) 3909 5090
Temperature of application	+10°C +35°C
Waiting time	None
Open time	Around 60 minutes
Step resistant after application	12-24 hours
Drying time	48 hours

### SAFETY ADVICE

Keep away from babies and infants. Dispose of waste in containers suitable for building materials.

### GUIDANCE

The information contained in this technical data sheet, resulting from our long experience, is purely indicative. Moreover, we advise that the user checks that the product is suitable for the purpose for which it is intended, and that they are responsible for its use.