

TECHNICAL DATA SHEET

REVISED: 01/12/2022

ADHESIVA S

POWDER ADHESIVES FOR WALL COVERINGS



Powder-based adhesive for use with wallpapers or paper-backed wallcoverings. Suitable for use together with other products from the ACM range.

Suitable for:

- All kinds of wallcoverings
- Paper-backed vinyl wallcoverings
- Expanded vinyl wallcoverings
- Heavyweight vinyl wallcoverings up to 600g/m²
- Duplex wallcoverings

TECHNICAL FEATURES

- + Stainless
- + Strong initial grab
- + High yield
- + Zero VOC (Volatile Organic Compounds)
- + Ready to use in 5 minutes from dilution

SURFACE PREPARATION

All surfaces must be clean and dry, absorbent and free from dust, paint and oil. Any cracks or holes in the wall must be filled with our light GLASTER filler and, in case of imperfections, smoothed with a normal plaster filler. We recommend using our PRIMER AC primer for preparation and cleaning, and our PRIMER SP (created for resistance to mold and bacteria) where the walls are damp.

PRODUCT PREPARATION

The product should be diluted in clean water in the proportions as shown in the following table:
(based on dilution of 250g of product)

DILUTION TABLE FOR 250G OF PRODUCT

WALL COVERING	DILUTION	m ²
Fixing	10 L	-
Wallpaper and lightweight vinyl	8 L	50-55
Non-woven/Glass fibre	7 L	45-50
Heavyweight vinyl	6 L	40-45

1. Stir the water vigorously
2. Tip the contents of the pack of powder into the water, continuing to stir.
3. Leave to settle for 3 minutes
4. Continue to stir
5. After a further 5 minutes the product is ready to be used

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 01/12/2022

ADHESIVA S

POWDER ADHESIVES FOR WALL COVERINGS



APPLICATION

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

CLEANING

It is recommended to wipe off any excess paste from joints and edges using a damp cloth. THIS PRODUCT DOES NOT LEAVE ANY MARKS.

CONTRA-INDICATIONS

Do not use this product on a non-absorbent surface, do not apply to damp or moldy walls, or where the surface has not been prepared adequately. Any excess paste on the surface must be wiped off immediately using a damp cloth.

PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
10111	250	g	Carton box	24
10111-500	500	g	Carton box	12
10111-1-12	1	kg	Carton box	12

STORAGE

The product is guaranteed for 60 months from the date of production. IT IS FROST RESISTANT. Store in a dry place.

PRODUCT TECHNICAL DATA

Description of Product	Powder
Colour	white
Percentage of Solids	100%
Customs Classification	3505 2030
Flame Resistance	no
Application Temperature	+5°C +40°C
Fixing Time	10-20 minutes
Open Time	20-30 minutes
Complete Drying Time	48 hours
Not Harmful	
Frost Resistant	

TECHNICAL DATA SHEET

REVISED: 01/12/2022

ADHESIVA S

POWDER ADHESIVES FOR WALL COVERINGS



FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.