

# TECHNICAL DATA SHEET

UPDATED TO: 24/05/2023

## PRIMER<sup>+</sup> CB GEL

### PRODUCTS FOR PREPARING FOR LAYING WALL COVERINGS



Special acrylic gel primer. PRIMER<sup>+</sup> CB GEL is particularly suitable as an anti-skid adhesion promoter for roller application on non-porous surfaces. It's based on PSA, pressure sensitive adhesive, suitable for fixing rubber underlayer to cement floors.

Suitable for:

- Application for carpet.
- Application on non-porous or sealed surfaces.
- Applications on drywall.
- Roller applications on glass and metal surfaces.
- Promoter of adhesion on non absorbent surface.

#### TECHNICAL FEATURES:

- + Ready to use
- + Odourless
- + Does not drip
- + Low VOC

#### SURFACE PREPARATION

PRIMER<sup>+</sup> CB GEL is ready to use in gel form.

#### PRODUCT APPLICATION

Proceed to the application of PRIMER<sup>+</sup> CB GEL on walls with short-haired wool roller. The product dries in 3 hours at 20/23°C. The weather varies depending on the temperatures and the characteristics of the environment.

Its GEL shape allows an easy and clean application, without dripping on the floor.

#### CONSUMPTION

Approx. 80-100 g/m<sup>2</sup> depending on the porosity of the substrate.

#### CLEANING

Clean tools with water immediately after use.

#### CONTRAINDICATIONS

It is not recommended for direct application on oily bases. Do not frost.

#### PACKING

PRODUCT CODE	WEIGHT	UNITS	PACKAGING
30207	2,5	Litres	Rectangular bucket
30208	5	Litres	Rectangular bucket
30209	10	Litres	Rectangular bucket

# TECHNICAL DATA SHEET

UPDATED TO: 24/05/2023

## PRIMER<sup>+</sup> CB GEL

PRODUCTS FOR PREPARING FOR LAYING WALL COVERINGS



### STORAGE

The product is guaranteed in the original packaging, under standard condition (+ 5 °C + 35 °C), for 24 months from the date of manufacture. It is important to store the product in a dry place and away from heat sources and direct sunlight.

### PRODUCT TECHNICAL DATA

Base	Water-based acrylic
Physical appearance and color	White gel
PH	7.0
Viscosity	15000-25000 cps
Percentage of solids	35%
Customs code	3209 1000
Application temperature	+5°C +40°C
Drying time	3 hours
Non-flammable	
Do not frost	

### FINAL REGULATIONS

Keep out of reach of children. Dispose of the residues in special containers for building materials.

### WARNINGS

The information contained in the technical sheet, although the result of our long experience, is only indicative. Therefore, those who intend to use it are required to evaluate whether the product is suitable for the application and assume responsibility for the use.