

TECHNICAL DATA SHEET

REVISED: 01/12/2022

TEXRECO EXTREME

READY MIXED ADHESIVES FOR WALL COVERINGS



Ready-mix adhesive for all types of wallcoverings. Suitable for absorbent and non-absorbent surfaces

Suitable for:

- Vinyl contract wall coverings with fabric or non woven backing with a weight up to 1 kg/m2
- Fiberglass wall coverings
- Paintable wall coverings
- Wallcoverings with cotton fabric support
- Difficult application

TECHNICAL FEATURES

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Very Low V.O.C. (Volatile Organic Compounds)

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light stucco GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid surface.

PRODUCT PREPARATION

Product is a ready-to-use product however when necessary, dilute it with clean water up to a maximum of 5/10%.

APPLICATION

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

CONSUMPTION

About 150 -250 gr/m2, depending on the porosity of the substrate

CLEANING

We recommend cleaning the wall coverings from excess adhesive and the joints with a wet sponge. Possible spillages of the adhesive should be removed immediately. We also recommend consulting the cleaning instructions of the wall covering's manufacturer before application. THE PRODUCT DOES NOT STAIN

CONTRAINDICATIONS

TEXRECO EXTREME is not suitable on imperfect prepared substrates or humid walls. We suggest, in case of humid wall, to prepare the surface with ACM PRIMER SP.

TECHNICAL DATA SHEET

REVISED: 01/12/2022

TEXRECO EXTREME

READY MIXED ADHESIVES FOR WALL COVERINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
10144	2,5	kg	Rectangular Bucket	6
10145	5	kg	Rectangular Bucket	2
10146	10	kg	Rectangular Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

Base	Starch
Appearance and colour	White cream
PH	6.5
Viscosity	65000-75000 cps
VOC	< 0.005 mg/ m3
Solids percentage	about 40%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	15-20 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.