

# **TECHNICAL DATA SHEET**

REVISED: 01/12/2022

## **VICEVERSA DIAMOND**

**PROFESSIONAL LINE FOR WALL COVERINGS**

**SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION**



Adhesive/resin/sealant with a modified silane polymer base, created to bind structural items together. Incorporates hydro-hardening properties.

Suitable for:

- Structural bonding in construction
- Sheet metals, guttering and facias
- Expansion joints between cement materials
- Polyurethane and polystyrene, even outdoors
- Bonding between non-absorbent materials, even outdoors (metals, glass, plastics)
- Strong suction effect

### **TECHNICAL FEATURES:**

- + Solvent free
- + Low elasticity
- + Strong initial grab
- + Low shrinkage
- + Low VOC emissions

### **SURFACE PREPARATION**

All grounds must be dry, absorbent, solid, free from dust, paints and oils. Any gaps should be filled with our ultra-light GLASTER filler.

### **PRODUCT PREPARATION**

Single component adhesive ready to use. Cut the nozzle from the cartridge and use an appropriate sealant gun.

### **PRODUCT APPLICATION**

Apply so that the adhesive contacts every required surface.

### **COVERAGE**

Approximately 15 linear metres per cartridge

### **CLEANING**

We recommend the use of a thinner

### **GUIDANCE**

- Not suitable for use at temperatures below +3°C
- Recommended operating temperature between + 10°C and + 35°C

---

[www.acm-italy.com](http://www.acm-italy.com)

# TECHNICAL DATA SHEET

REVISED: 01/12/2022

## VICEVERSA DIAMOND

PROFESSIONAL LINE FOR WALL COVERINGS

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



### PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30129B (white)	300	ml	Cartridge	24
30129T (transp.)	300	ml	Cartridge	24

### STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

### PRODUCT TECHNICAL DATA

Base	Modified Silane Polymer
Physical Appearance	Extra white colour or clear
Percentage of solids	Approx 80%
Customs Code	3909 5090
Operating Temperature	+10°C +35°C
Waiting Time	None
Open Time	Approx 30-40 minutes
Total Drying Time	48/72 hours

### SAFETY ADVICE

Keep away from babies and small children. Dispose of waste in containers suitable for building materials.

### ADVISORY

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.

[www.acm-italy.com](http://www.acm-italy.com)