

TECHNICAL DATA SHEET

REVISED: 17/04/2023

VK P ECO

SEALANTS AND MOUNTING



Acrylic based structural adhesive, for polystyrene, polyurethane baseboards and tiles. Strong suction cup effect and strong initial tack.

Suitable for:

- Wood, PVC and ceramic baseboard applications
- Tiles and Wall Ceramics applications
- Polystyrene and polyurethane panels, frames and rosettes
- Cork and thermo-acoustic materials

TECHNICAL FEATURES:

- + No highly flammable solvents
- + Paintable
- + Strong suction cup effect
- + No nails support required

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler GLASTER.

ADHESIVE PREPARATION

Mono-component adhesive and ready-for-use. Cut the seal of the cartridge and use a special caulking gun for cartridges

APPLICATION

Apply the product all over the contact surface.

CONSUMPTION

- About 15 m linear per cartridge
- 200-300 g/m² when applied by trowel

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRAINDICATIONS

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) - Telefono +39 02 90361148 r.a. - Fax +39 02 9013173 - e-mail: info@acm-italy.com

C.C.I.A.A. MI-1952713 - Cod. Fisc. e P. IVA 07352030964

TECHNICAL DATA SHEET

REVISED: 17/04/2023

VK P ECO

SEALANTS AND MOUNTING



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30024	300	ml	Cartridge	24
30026	700	gr	Small bucket	24
30027	6	kg	Bucket	1
30028	13	kg	Bucket	1
30029	20	kg	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Base	Acrylic
Appearance and colour	Extra White or coloured on request
Solids percentage	about 80%
Customs code	3506 9100
Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 30-40 min
Setting Time	48/72 hours

FINAL REGULATIONS

Keep out of reach of children. Discharge the waste in special containers for building materials

DISCLAIMER

The above-mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore, before using, it is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) - Telefono +39 02 90361148 r.a. - Fax +39 02 9013173 - e-mail: info@acm-italy.com

C.C.I.A.A. MI-1952713 - Cod. Fisc. e P. IVA 07352030964